



規格 SPECIFICATIONS

- Ⓐ
1. RATING : 10A 250VAC
2. WITHSTAND VOLTAGE : AC 2000V 1Min
3. INSULATION RESISTANCE : MORE THAN 100MΩ (at DC 500V)
4. OPERATING TEMPERATURE : -25° C TO +85° C (MAX)
5. SAFETY :

- Ⓑ
1. RATING : 10A 125VAC/250VAC
16A 250VAC
-

2. CONTACT RESISTANCE : 30mΩ Max .
3. INSULATION RESISTANCE : DC 500V 100MΩ Min .
4. WITHSTAND VOLTAGE : AC 1000V 1 Min
5. OPERATION FORCE : 800±300 g .
6. ELECTRICAL LIFE : 10,000 Cycles At Full Load .
7. OPERATING TEMPERATURE RANGE : -25°C~+85°C
8. SOLDERING : 280°C FOR 3 Sec .

B	JS-60B	1	16A 250VAC	UL, CSA, VDE	
A	JR-101-1FS	1	10A 250VAC	UL, VDE, S, D, N, FI	
編號	零件名稱	數量	規格	安規認證	備註
設計	L.chun-ting 911108	品名	承認圖	無註記公差	第三
製圖	L.chun-ting 911108				