



NON-SHORTING  
SCHEMATIC

X =

|        |                                                |                 |                   |  |           |
|--------|------------------------------------------------|-----------------|-------------------|--|-----------|
| ISSUED | SPECIFICATION (INITIAL)                        | TITLE:          | SLIDE SWITCH 1P2T |  |           |
|        | RATING: AC 125V 3A                             | MODEL NO:       | WK-12F25-G        |  |           |
|        | CONTACT RESISTANCE: Not more than 30mΩ         | UNIT: mm        | DWN               |  |           |
|        | INSULATION RESISTANCE: 500MΩ at 500V DC        | SCALE: 2 : 1    | CHK'd             |  |           |
|        | WITHSTAND VOLTAGE AC 1000V for 1 min           | TOLERANCE: ±0.2 | APPD.             |  |           |
|        | OPERATION FORCE: 300±200g                      |                 |                   |  |           |
|        | SWITCHING LIFE: 10,000 Cycles(6-10c/m loading) |                 |                   |  |           |
| By:    | 銳永企業有限公司 E-YUNG ENTERPRISE CO., LTD.           |                 |                   |  | DRWS NO:  |
| DATE:  |                                                |                 |                   |  | 991277-00 |

The material contained in this drawing is the property of PIC. Any use other than that specifically authorized by PIC is prohibited. The above drawing is subjected to change for improvement without prior notice.

ENG-F-51